

END FACE STRUCTURE OF OPTICAL FIBER AND OPTICAL FIBER

Publication number: JP2002323625

Publication date: 2002-11-08

Inventor: SASAOKA HIDEYORI; HASEGAWA TAKEMI; ONISHI MASASHI; ISHIKAWA SHINJI

Applicant: SUMITOMO ELECTRIC INDUSTRIES

Classification:

- international: **G02B6/02; C03B37/15; G02B6/032; G02B6/02; C03B37/10; (IPC1-7): G02B6/10; G02B6/20**

- European: **C03B37/15; G02B6/02P**

Application number: JP20010128151 20010425

Priority number(s): JP20010128151 20010425

Also published as:



EP1255137 (A2)

US6868213 (B2)


US2002159734 (A1)

EP1255137 (A3)

[Report a data error here](#)

Abstract of JP2002323625

PROBLEM TO BE SOLVED: To provide an end face structure of an optical fiber, that can reduce deterioration of optical characteristics and also to provide the optical fiber. **SOLUTION:** The optical fiber 1 consists of a hollow core part 2 and a clad part 3 surrounding this hollow core part 2, with the refractive index of the hollow core part 2 made lower than that of the clad part 3. The hollow core part 2 is, in its structure, blocked at both end faces and formed with sealed parts 5. This sealed parts 5 are formed for example by heating the optical fiber 1 and softening the clad part 3. As a result, it prevents foreign matters or the like from entering the hollow core part 2. To both end faces of the optical fiber 1, ferrules 6 of an optical connector are attached respectively.



Data supplied from the **esp@cenet** database - Worldwide

